

## SSC122: FIBC Bulk Bags Technical Specification

|                            |   |
|----------------------------|---|
| <b>Bag size :</b>          | <b>90 X 90 X 120 cm</b>                         |
| <b>Safe Working Load :</b> | <b>1250 Kg</b>                                  |
| <b>Safety Factor:</b>      | <b>5:1</b>                                      |
| <b>Fabric GSM :</b>        | <b>160+30 GSM</b>                               |
| <b>Lamination:</b>         | <b>30 GSM Lamination inside</b>                 |
| <b>Bag type:</b>           | U-panel construction with 4 X corner loops.     |
| <b>Fabric type:</b>        | Circular woven (Tubular).                       |
| <b>Fabric colour:</b>      | White.  |
| <b>Loop length:</b>        | Loop length: 0+30 cm                            |
| <b>Loop width:</b>         | 40 mm   |
| <b>Loop colour:</b>        | White   |
| <b>Filling spout :</b>     | Diameter 40X50 cm with white web tie (2X50 cm). |
| <b>Discharge spout:</b>    | Diameter 40X50 cm with white web tie (2X50 cm). |
| <b>Sewing thread:</b>      | White.  |
| <b>Pouch:</b>              | A 4 (One Pc) attached with top seam.            |
| <b>Bag weight:</b>         | 1790 grams ( +/-4%).                            |
| <b>Packing:</b>            | 205 Pcs/Pallet                                  |