

## SSL122: FIBC Bulk Bags - Top & Bottom Spout

<b>Bag size :</b>	<b>90 X 90 X 120 cm</b>
<b>Safe Working Load :</b>	<b>1250 Kg</b>
<b>Safety Factor:</b>	<b>5:1</b>
<b>Fabric GSM :</b>	<b>160 GSM</b>
<b>Liner:</b>	<b>Polythene Inner Liner 80 or 100 micron (Sewn with 8 tabs, sewn at mouth of top spout)</b>
<b>Bag type:</b>	U-panel construction with 4 X corner loops.
<b>Fabric type:</b>	Circular woven.
<b>Fabric colour:</b>	White.
<b>Loop length:</b>	Loop length: 0+30 cm
<b>Loop width:</b>	40 mm
<b>Loop colour:</b>	White
<b>Filling spout :</b>	Diameter 40X50 cm with white web tie (2X50 cm).
<b>Discharge spout:</b>	Diameter 35X50 cm with white web tie (2X50 cm).
<b>Sewing thread:</b>	White.
<b>Pouch:</b>	A 4 (One Pc) attached with top seam.
<b>Bag weight:</b>	2553 grams ( +/-4%).
<b>Packing:</b>	135 or 125 pcs/ Pallet