

SYDNEY3/8 Lancaster St,
INGLEBURN, NSW 2565
T: (02) 9618 1264**MELBOURNE**2/46 Barretta Rd,
RAVENHALL, VIC 3023
T: (03) 8361 9095**PERTH**8/49 Biscayne Way
JANDAKOT, WA 6164,
T: (08) 9414 1149

BULK BIN 155: Open Top & Closed Bottom



Suitable for construction, demolition, roof repair, crane lifting, rubbish removal.

Bag size: 150 x 150 x 100 cm	Safe Working Load: 1250 kg for Multi Trips & 1500 Kgs for Single Trip
Test Certification: AS 3668-1989 Australian Standard	Fabric GSM: 180+0
Safety Factor: 6:1 (multi trip)/ 5:1 (single trip)	Liner: None
Lamination: None	Loop length: 50 cm (White) full running loops through sides and bottom
Bag type: 4 loops	Fabric type: U-Panel
Fabric colour: White	Discharge: Closed Bottom
Filling: Open or Flap Top	Bag weight: 3125 grams (+/-4%)
Sewing thread: White	Pouch: A 4 attached with top seam.
Packing: 120 pcs / pallet	

The specification is standard for this product and it rarely varies with different orders.

bulkbags.com.auBULKBAGS AUSTRALIA PTY LTD
ABN 20 607 889 136 | ACN 607 889 136